

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
1 April 2004 (01.04.2004)

PCT

(10) International Publication Number
WO 2004/027438 A1

(51) International Patent Classification⁷: **G01R 31/30**

(21) International Application Number:
PCT/IB2003/003553

(22) International Filing Date: 8 August 2003 (08.08.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
02078906.1 20 September 2002 (20.09.2002) EP

(71) Applicant (for all designated States except US): **KONINKLIJKE PHILIPS ELECTRONICS N.V.** [NL/NL];
Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **RIUS VAZQUEZ, Josep** [ES/ES]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). **PINEDA DE GYVEZ, Jose, D., J.** [MX/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(74) Agent: **DULJVESTIJN, Adrianus, J.**; Philips Intellectual Property & Standards, Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR DETERMINING IDDQ



(57) Abstract: A test apparatus for testing a device under test (DUT) to detect a defect comprises a measurement circuit (ME), a threshold circuit (TH), and a control circuit (CG). The measurement circuit (ME) comprises a counter (C1) which counts clock pulses (CLK) during a count period (TC) to obtain a counted number (N) of clock pulses (CLK). The count period (TC) has a start determined by the start (t1) of a testing cycle which occurs at the instant a switch (S) which is coupled to an terminal (IN) of the device under test (DUT) removes a power supply voltage (VDD) from the terminal (IN) and the voltage (VDD') at the terminal (IN) starts decaying. An end of the count period (TC) is determined by an instant (t2) a comparator (COM1) detects that the voltage (VDD') at the terminal (IN) crosses a reference value (VREF). The control circuit (CG) generates the clock signal (CLK) and/or a reference number (NTH) taking into account the variability of the manufacturing process of the circuit under test (CUT). The threshold circuit (TH) generates a pass/fail signal (PF) by comparing the counted number (N) and the reference number (NTH).



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.